

Lembar data produk

Spesifikasi



APC Back-UPS Pro 900VA, 230V, AVR, LCD, 6 IEC outlets

BR900MI

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|------------------------------------|
| Main Input Voltage | 230 V |
| Rated power in W | 540 W |
| Rated power in VA | 900 VA |
| Product or component type | Uninterruptible power supply (UPS) |
| Output connection type | 6 IEC 60320 C13 |
| Battery type | Lead-acid battery |

Batteries & Runtime

| | |
|--|---------------------------|
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 12 h |
| Number of battery replacement quantity | 1 |
| Battery voltage | 12 V |
| Battery capacity | 9.4 Ah |
| Battery charger power | 11 W rated |
| Battery power in VAh | 128 VAh runtime |
| Battery life | 3...5 year(s) |
| Replacement battery | APCRBC164 |
| Extended runtime | 0 |

General

| | |
|-------------------------------------|--------------------------|
| Provided equipment | user manual USB cable |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|--------------------|
| Height | 19 cm |
| Width | 9.1 cm |
| Depth | 31 cm |
| Product weight | 7.1 kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | No |

Input

| | |
|----------------------------|--------------------------------|
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Input voltage limits | 176...294 V |
| Maximum input current | 10 A |
| Switching current capacity | 10 A |

Output

| | |
|----------------------------------|-------------------------------------|
| Maximum configurable power in W | 540 W |
| Output frequency | 50/60 Hz +/- 1 Hz sync to mains |
| UPS type | Line interactive |
| Wave type | Stepped approximation to a sinewave |
| Maximum configurable power in VA | 900 VA |
| Transfer time | 10 ms typical : 12 ms maximum |

Conformance

| | |
|------------------------|--|
| Product certifications | A-Tick C-Tick CE EAC RCM TISI |
| Marking | GS Mark |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 45 dBA |
| Heat dissipation | 16.4 Btu/h |

Communications & Management

| | |
|---------------|--|
| Control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|-------------------|---|
| Noise suppression | Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous |
|-------------------|---|

Packing Units

| | |
|------------------------------|----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 25.5 cm |
| Package 1 Width | 14.3 cm |
| Package 1 Length | 44 cm |
| Package 1 Weight | 8 kg |
| SCC14 | 10731304346941 |

Offer Sustainability

| | |
|-----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---|
| Warranty | 2 years repair or replace, 3 years repair or replace for European Union countries |
|----------|---|

Penggantian yang disarankan