

# ViewSonic® LAYAR LCD VX2728J-2K

## Fitur Utama

- Fast IPS Display with HDR10
- AMD FreeSync™ Premium for smooth gameplay
- VESA AdaptiveSync for tear-free gaming experience
- VESA ClearMR for clarity of action
- Rapid 0.5ms MPRT for crisp image



## Deskripsi Produk

No matter how often you game or when you game, you always win with the Omni VX2728J-2K's. The triple certification of AMD FreeSync™ Premium, VESA Adaptive Sync, and VESA clearMR allows you to savor distortion-free gaming and enhanced clarity. The sharp frames and outstanding color performance are delivered by a fast IPS panel, while the VX2728J-2K's high 180Hz refresh rate supports smooth visuals and minimal input lag. You may think it doesn't get better than this, but it does. Not only will you get the job done — be it grueling gaming sessions, video and photo editing, or office assignments — you'll be working on a sleek, beautifully designed monitor.

**Kunjungi Kami** [www.viewsonic.com](http://www.viewsonic.com)

**TAMPILAN**

Display Size (in.):	27
Viewable Area (in.):	27
Jenis Panel:	IPS Technology
Resolusi:	2560 x 1440
Jenis Resolusi:	QHD (Quad HD)
Rasio Kontras Statis:	1,000:1 (typ)
Rasio Kontras Dinamis:	80M:1
Sumber cahaya:	LED
Kecerahan:	250 cd/m <sup>2</sup> (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	0.5ms
Sudut Pandang:	178° horizontal, 178° vertical
Backlight Life (Jam):	30000 Hrs (Min)
Lengkungan:	Flat
Refresh Rate (Hz):	180
Variable Refresh Rate Technology:	FreeSync Premium, AdaptiveSync
Filter Cahaya Biru:	Yes
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 90% coverage (Typ) NTSC: 93% size (Typ) sRGB: 131% size (Typ)
Ukuran Piksel:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**KESESUAIAN**

Resolusi PC (max):	2560x1440
Resolusi Mac® (maks):	2560x1440
Sistem Operasi PC:	Windows 10/11 certified; macOS tested
Resolusi Mac® (min):	2560x1440

**KONEKTOR**

3.5mm Audio Out:	1
HDMI 2.0:	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

**AUDIO**

Speaker Internal:	2Watts x2
-------------------	-----------

**POWER**

Mode Eco (Hemat):	22W
Eco Mode (optimized):	26W
Konsumsi (khas):	31W
Konsumsi (maks):	35W
Tegangan:	AC 100-240V
Stand-by:	0.3W
Sumber Daya listrik:	External Power Adaptor

**PERANGKAT KERAS TAMBAHAN**

Slot Kunci Kensington:	1
Cable Organization:	Yes

**KONTROL**

Kontrol Fisik:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
Pada Tampilan Layar:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Suhu:	32°F to 104°F (0°C to 40°C)
Kelembaban (tanpa kondensasi):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**SINYAL INPUT**

Frekuensi Horizontal:	HDMI (v2.0): 30 ~ 218KHz, DisplayPort (v1.4): 30 ~ 243KHz
Frekuensi Vertikal:	HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 180Hz

**VIDEO INPUT**

Sinkronisasi Digital:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
-----------------------	--

**ERGONOMIS**

Penyesuaian Tinggi (mm):	130
Memutar:	30°
Miring (Maju / Mundur):	-5° / 20°
Pivot (Kanan / Kiri):	90° / 0°

**BERAT (IMPERIAL)**

Net (lbs):	10.4
Bersih Tanpa Dudukan (lbs):	8
Gross (lbs):	14.3

**WEIGHT (METRIC)**

Net (kg):	4.7
Jaring Tanpa Dudukan (kg):	3.7
Gross (kg):	6.5

**DIMENSI (IMPERIAL) (WXHxD)**

Kemasan (in.):	26.8 x 18.1 x 6.8
Fisik (in.):	24.2 x 17.24~22.36 x 8.1
Fisik Tanpa Berdiri (masuk):	24.2 x 14.3 x 1.8

**DIMENSI (METRIK) (WXHxD)**

Kemasan (mm):	680 x 460 x 173
Fisik (mm):	615 x 438~568 x 207
Physical Without Stand (mm):	615 x 364 x 46

**UMUM**

Regulasi:	cTUVus, FCC-B, ICES003, CEC, NRCAN, RoHS, REACH, WEEE, BSMI, RCM, VCCI, PSE
ISI PAKET:	VX2728J-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Daur Ulang / Pembuangan:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market